



MATERIAL SAFETY DATA SHEET

2-Methyl-1-propanol, 99%

Section 1 - Chemical Product and Company Identification

MSDS Name:	2-Methyl-1-propanol, 99%
Synonyms:	Isobutyl alcohol; Isobutanol

Company Identification:	Hazel Mercantile Limited
Company Identification: (INDIA)	701, Embassy Centre , Nariman Point , Mumbai – 400 021
For information in the INDIA, call:	+91-22-2282 4444 (50 Lines)

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name:	%	EINECS#
78-83-1	2-Methyl-1-propanol	99%	201-148-0

Hazard Symbols:	XI
	
Risk Phrases:	10 37/38 41 67

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Flammable. Irritating to respiratory system and skin. Risk of serious damage to eyes. Vapours may cause drowsiness and dizziness.

Potential Health Effects

Section 4 - First Aid Measures

Eyes:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin:	Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Ingestion:	Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Get medical aid.
Inhalation:	Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
Notes to Physician:	

Section 5 - Fire Fighting Measures

General Information:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors can travel to a source of ignition and flash back. Will burn if involved in a fire.
Extinguishing Media:	In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam. Use water spray to cool fire-exposed containers.



Section 6 - Accidental Release Measures

General Information:	Use proper personal protective equipment as indicated in Section 8.
Spills/Leaks:	Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition.

Section 7 - Handling and Storage

Handling:	Use spark-proof tools and explosion proof equipment. Do not breathe dust, vapor, mist, or gas. Do not get in eyes, on skin, or on clothing. Use only in a chemical fume hood.
Storage:	Keep away from sources of ignition. Store in a cool, dry place. Store in a tightly closed container. Flammables-area.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls:	Use adequate ventilation to keep airborne concentrations low.
Exposure Limits	
	CAS# 78-83-1:
	United Kingdom, WEL - TWA: 50 ppm TWA; 154 mg/m3 TWA United Kingdom, WEL - STEL: 75 ppm STEL; 231 mg/m3 STEL
	United States OSHA: 100 ppm TWA; 300 mg/m3 TWA
	Belgium - TWA: 50 ppm VLE; 154 mg/m3 VLE
	France - VME: 50 ppm VME; 150 mg/m3 VME
	Germany: 100 ppm TWA; 310 mg/m3 TWA
	Japan: 50 ppm OEL; 150 mg/m3 OEL
	Malaysia: 50 ppm TWA; 152 mg/m3 TWA
	Netherlands: 50 ppm MAC; 150 mg/m3 MAC
	Spain: 50 ppm VLA-ED; 154 mg/m3 VLA-ED

Personal Protective Equipment	
Eyes:	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin:	Wear appropriate protective gloves to prevent skin exposure.
Clothing:	Wear appropriate protective clothing to prevent skin exposure.
Respirators:	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Section 9 - Physical and Chemical Properties

Physical State:	Clear liquid
Color:	APHA: 10 max
Odor:	Not available
pH:	Not available
Vapor Pressure:	11.7 mbar @ 20 deg C
Viscosity:	Not available
Boiling Point:	108 deg C @ 760.00mm Hg (226.40°F)
Freezing/Melting Point:	-108 deg C (-162.40°F)
Autoignition Temperature:	430 deg C (806.00 deg F)
Flash Point:	28 deg C (82.40 deg F)
Explosion Limits: Lower:	1.60 vol %



Explosion Limits: Upper:	10.90 vol %
Decomposition Temperature:	Not available
Solubility in water:	95 g/l (20°C)
Specific Gravity/Density:	0.8030g/cm3
Molecular Formula:	C4H10O
Molecular Weight:	74.12

Section 10 - Stability and Reactivity

Chemical Stability:	Stable under normal temperatures and pressures.
Conditions to Avoid:	Incompatible materials, ignition sources.
Incompatibilities with Other Materials	Strong oxidizing agents, acid chlorides, acid anhydrides.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide.
Hazardous Polymerization	Will not occur.

Section 11 - Toxicological Information

RTECS#:	CAS# 78-83-1: NP9625000
LD50/LC50:	RTECS: CAS# 78-83-1: Inhalation, mouse: LC50 = 15500 mg/m3/2H; Inhalation, rabbit: LC50 = 2630 mg/m3/4H; Inhalation, rat: LC50 = 19200 mg/m3/4H; Oral, mouse: LD50 = 3500 mg/kg; Oral, rabbit: LD50 = 74.1 mg/kg; Oral, rat: LD50 = 2460 mg/kg; Skin, rabbit: LD50 = 3400 mg/kg; . Other: Inhalation, rat: LCL0 = 8000 ppm/4H Skin, rabbit: 20 mg/24H moderate Eye, rabbit: 2 mg open severe Eye, rabbit: 2 mg/24H severe
Carcinogenicity:	2-Methyl-1-propanol - Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.
Other:	See actual entry in RTECS for complete information.

Section 12 - Ecological Information

Ecotoxicity:	Not available
---------------------	---------------

Section 13 - Disposal Considerations

Dispose of in a manner consistent with federal, state, and local regulations.

Section 14 - Transport Information

	IATA	IMO	RID/ADR
Shipping Name:	ISOBUTANOL	ISOBUTANOL	ISOBUTANOL
Hazard Class:	3	3	3
UN Number:	1212	1212	1212
Packing Group:	III	III	III

USA RQ: CAS# 78-83-1: 5000 lb final RQ; 2270 kg final RQ



Section 15 - Regulatory Information

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: XI

Risk Phrases:

- R 10 Flammable.
- R 37/38 Irritating to respiratory system and skin.
- R 41 Risk of serious damage to eyes.
- R 67 Vapours may cause drowsiness and dizziness.

Safety Phrases:

- S 7/9 Keep container tightly closed and in a well-ventilated place.
- S 13 Keep away from food, drink and animal feeding stuffs.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 37/39 Wear suitable gloves and eye/face protection.
- S 46 If swallowed, seek medical advice immediately and show this container or label.

WGK (Water Danger/Protection)

- CAS# 78-83-1: 1

Canada

- CAS# 78-83-1 is listed on Canada's DSL List

US Federal

- TSCA
- CAS# 78-83-1 is listed on the TSCA Inventory.

Section 16 - Other Information

MSDS Creation Date: October 15, 2007

Revision #0 Date

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.