



MATERIAL SAFETY DATA SHEET


Methyl Isobutyl Ketone (MIBK)

Section 1 - Chemical Product and Company Identification

MSDS Name:	Methyl Isobutyl ketone, 99.5%
Synonyms:	Hexone, Isopropylacetone, 4-Methyl-2-oxopentane, MIBK.
Company Identification:	Hazel Mercantile Limited
Company Identification: (INDIA)	701, Embassy Centre , Nariman Point , Mumbai – 400 021
For information in the INDIA, call:	+91-22-2282 4444 (50 Lines)

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name:	%	EINECS#
108-10-1	4-Methyl-2-pentanone	99.5%	203-550-1

Hazard Symbols:	XN F
	
Risk Phrases:	11 20 36/37 66

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Highly flammable. Irritating to eyes and respiratory system. Harmful by inhalation. Repeated exposure may cause skin dryness or cracking.

Potential Health Effects

Eye:	Causes eye irritation.
Skin:	May cause skin irritation.
Ingestion:	May cause irritation of the digestive tract.
Inhalation:	Harmful if inhaled. Causes respiratory tract irritation.
Chronic:	

Section 4 - First Aid Measures

Eyes:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin:	Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Ingestion:	Get medical aid. Wash mouth out with water.
Inhalation:	Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.
Notes to Physician:	



Section 5 - Fire Fighting Measures

General Information:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Will burn if involved in a fire. Flammable liquid and vapor. May form explosive peroxides.
Extinguishing Media:	In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam.

Section 6 - Accidental Release Measures

General Information:	Use proper personal protective equipment as indicated in Section 8.
Spills/Leaks:	Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition. Use a spark-proof tool.

Section 7 - Handling and Storage

Handling:	Use spark-proof tools and explosion proof equipment. Avoid breathing dust, vapor, mist, or gas. Avoid contact with skin and eyes.
Storage:	Keep away from sources of ignition. Store in a cool, dry place. Store in a tightly closed container. Flammables-area. May form explosive peroxides on prolonged storage.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls:

Use adequate ventilation to keep airborne concentrations low.

Exposure Limits

CAS# 108-10-1:
United Kingdom, WEL - TWA: 50 ppm TWA; 208 mg/m3 TWA United Kingdom, WEL - STEL: 100 ppm STEL; 416 mg/m3 STEL
United States OSHA: 100 ppm TWA; 410 mg/m3 TWA
Belgium - TWA: 20 ppm VLE; 83 mg/m3 VLE Belgium - STEL: 50 ppm VLE; 208 mg/m3 VLE
France - VME: 20 ppm VME; 83 mg/m3 VME France - VLE: 50 ppm VLE; 208 mg/m3 VLE
Germany: 20 ppm TWA; 83 mg/m3 TWA Germany: skin notation
Japan: 50 ppm OEL; 200 mg/m3 OEL
Malaysia: 50 ppm TWA; 205 mg/m3 TWA
Netherlands: 50 ppm STEL; 208 mg/m3 STEL Netherlands: 25 ppm MAC; 104 mg/m3 MAC
Spain: 20 ppm VLA-ED; 83 mg/m3 VLA-ED Spain: 50 ppm VLA-EC; 208 mg/m3 VLA-EC

Personal Protective Equipment

Eyes:	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin:	Wear appropriate protective gloves to prevent skin exposure.
Clothing:	Wear appropriate protective clothing to minimize contact with skin.
Respirators:	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.



Section 9 - Physical and Chemical Properties

Physical State:	Clear liquid
Color:	APHA: 15 max
Odor:	camphor - sweetish odor
pH:	Not available
Vapor Pressure:	15.7 mm Hg @ 20 deg C
Viscosity:	Not available
Boiling Point:	116 deg C @ 760.00mm Hg (243.32°F)
Freezing/Melting Point:	-84 deg C (-119.20°F)
Autoignition Temperature:	460 deg C (860.00 deg F)
Flash Point:	14 deg C (57.20 deg F)
Explosion Limits: Lower:	1.40 vol %
Explosion Limits: Upper:	7.50 vol %
Decomposition Temperature:	Not available
Solubility in water:	Not available.
Specific Gravity/Density:	.8010g/cm3
Molecular Formula:	C6H12O
Molecular Weight:	100.16

Section 10 - Stability and Reactivity

Chemical Stability:	Stable at room temperature in closed containers under normal storage and handling conditions.
Conditions to Avoid:	Incompatible materials, ignition sources, exposure to air, excess heat.
Incompatibilities with Other Materials	Oxidizing agents, reducing agents, strong bases, potassium tert-butoxide.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide.
Hazardous Polymerization	Has not been reported.

Section 11 - Toxicological Information

RTECS#:	CAS# 108-10-1: SA9275000
LD50/LC50:	RTECS: CAS# 108-10-1 : Draize test, rabbit, eye: 40 mg Severe; Draize test, rabbit, eye: 100 uL/24H Moderate; Draize test, rabbit, skin: 500 mg/24H Mild; Inhalation, mouse: LC50 = 23300 mg/m3; Inhalation, mouse: LC50 = 23300 mg/m3; Inhalation, rat: LC50 = 100 gm/m3; Oral, mouse: LD50 = 1900 mg/kg; Oral, mouse: LD50 = 2850 mg/kg; Oral, rat: LD50 = 2080 mg/kg; Oral, rat: LD50 = 4600 mg/kg;
Carcinogenicity:	4-Methyl-2-pentanone - Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.
Other:	See actual entry in RTECS for complete information. The toxicological properties have not been fully investigated.



Section 12 - Ecological Information

Ecotoxicity:	Not available
Other:	On soil, substance volatilizes and biodegrades. In water, substance volatilizes and biodegrades. Redwinged blackbird, orl LD50=100mg/kg. Goldfish LC50=460mg/L/24H.

Section 13 - Disposal Considerations

Dispose of in a manner consistent with federal, state, and local regulations.

Section 14 - Transport Information

	IATA	IMO	RID/ADR
Shipping Name:	METHYL ISOBUTYL KETONE	METHYL ISOBUTYL KETONE	METHYL ISOBUTYL KETONE
Hazard Class:	3	3	3
UN Number:	1245	1245	1245
Packing Group:	II	II	II

USA RQ: CAS# 108-10-1: 5000 lb final RQ; 2270 kg final RQ

Section 15 - Regulatory Information

European/International Regulations
European Labeling in Accordance with EC Directives
Hazard Symbols: XN F
Risk Phrases:
➤ R 11 Highly flammable.
➤ R 20 Harmful by inhalation.
➤ R 36/37 Irritating to eyes and respiratory system.
➤ R 66 Repeated exposure may cause skin dryness or cracking.
Safety Phrases:
➤ S 9 Keep container in a well-ventilated place.
➤ S 16 Keep away from sources of ignition - No smoking.
➤ S 29 Do not empty into drains.
WGK (Water Danger/Protection)
➤ CAS# 108-10-1: 1
Canada
➤ CAS# 108-10-1 is listed on Canada's DSL List
US Federal
➤ TSCA
➤ CAS# 108-10-1 is listed on the TSCA Inventory.



Section 16 - Other Information

MSDS Creation Date:	7/16/1996
----------------------------	-----------

Revision #0 Date	Original.
-------------------------	-----------

MSDS Creation Date:	October 15, 2007
----------------------------	------------------

Revision #0 Date	
-------------------------	--

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.